



4280T

TRACKED STOCKPILER

The 4280T is the ideal mobile stockpiling solution for a large range of applications. This heavy duty, but versatile machine can be setup in super fast time.

Featuring a unique 'Boomerang' design, the feed boot height can be adjusted without altering the head drum position. This ensures maximum flexibility without losing stockpile capacity.

The 4280T can receive material directly from a crusher or screen or be installed in a close circuit application. With its Hi-Torque drive system this machine can be fed direct by a Wheeled Loader or Excavator (requires fitting of Direct Feed Hopper). It also integrates easily into the Tesab range of crushers and screeners making it the ideal solution in any situation.

Features & Benefits

- Up to 600+ tonnes per hour production rate
- Unique 'Boomerang' system allows a stockpile capacity of 2162m³ (3460 Tonnes @1.6T/ m³)
- Hi-Torque drive and engine size combine to reduce fuel consumption
- Range of optional extras available



PERFORMANCE SPECIFICATION * Depending on application

Operating Rate	Stockpile Height	Stockpile Capacity
600+ TPH*	37' (11,330mm)	7093' (2162 m ³)
Conveyor Width	Conveyor Length	
42" (1050mm)	77' (23,500mm)	

DIMENSION SPECIFICATION* * Depending on material density and set-up

TRANSPORT DIMENSIONS		
Height	Width	Length
8' 5" (2590mm)	7' 4" (2250mm)	39' 4" (12,000mm)
MAX WORKING DIMENSIONS		
Width	Length	Weight (est)
7' 4" (2250mm)	69' 5" (21,170mm)	15,800kgs (34,833 lbs)